

DISTRIBUTED BY JUST LIFE GROUP LTD



### PRODUCT DESCRIPTION

Tubular daylighting device to transfer daylight into any small space.

### KEY BENEFITS

- **More light:** Solatube's advanced optics mean more light is collected when you need it from early morning to late afternoon.
- **Dimmable:** With our daylight dimmer accessories you take control of the sun.
- **Round corners and horizontally:** With angle adapters and highly reflective tubes there are no barriers to where the light can go.
- **Flexible install:** Domes can be installed almost anywhere on your roof, they don't need to be right near the diffuser.
- **Modern look:** With multiple diffuser options to choose from including square there's a look to suit every space.
- **Peace of mind:** As penetration specialists we offer a 10-year leak proof guarantee using our proprietary roof flashings.

### APPLICATIONS

*This system is suitable, but not limited to the following areas:*

- Dark areas or internal rooms which require daylight
- Bedroom, lounge, dining, kitchen, large bathrooms
- Internal room requiring daylight to meet building code G7
- New builds and retrofit


### PRODUCT COMPLIANCE

- B2, E2, F2, G7 and H1
- AS 4285
- ISO 9001
- BRANZ 665

### ACCESSORIES



LED light kit



407FD fire damper


 Solar daylight dimmer  
 0-10V dimmer


0-90 degree bend



A variety of additional lenses, diffusers, square options and thermal panel

### SPECIFICATIONS

Recommended Maximum Tube Run:	9m
Diameter:	350mm
Recommended Maximum Ceiling Height:	<3m
Minimum Roof Space:	NA
R Value (NFRC):	0.35 - 0.48* *with thermal insulation panel
Visual Transmittance:	0.51
SHGC (Solar Heat Gain Coefficient):	0.23
Wind Zone:	Very high
Flashing Available:	5-45deg (self flashing or tray) and <5deg (tray or curb mount)
Dome Technology:	UV and impact resistant Impact modified acrylic blend. Raybender 3000 technology Light tracker reflector
Tube Technology:	Spectralight infinity tubing
Reflectance:	99.7%

## LIMITATIONS

- Requires access to the roof.
- Tube length should be no longer than 9m.

## INSTALLATION TO BE CARRIED OUT BY AUTHORISED HOMETECH INSTALLER

- Roof mounted flashing system and top collection dome to be installed before scaffolding and edge protection is removed if possible.
- Clear path, free of other services, is to be provided by the main contractor to the tubular daylight device's ceiling location.
- Hometech to do final fit once ceiling has been installed and painted.
- Safe working at height practices to be followed.

## WARRANTY (SEE WARRANTY DETAILS FOR MORE INFORMATION)

- 10 Years LEAK PROOF GUARANTEE
- 10 Years for materials and workmanship
- 5 Years for accessories

## CAD DRAWING (FURTHER VARIATIONS AVAILABLE ON THE WEBSITE)

